



C5TTM000

UNI 12825:4/3 /A/1

C5TTM 4x4 raised access floor system, FSC 100% recycled chipboard core, density 700/750 kg/m³ totally encased in two steel galvanized tray, thickness 0,35 mm, assembled with bi-component water base glue, reinforced with quadruple folded patented perimeter joint located in the upper part of the panel itself. Panels produced in accordance with quality management and environmental system as UNI EN ISO 9001:2015 and UNI EN ISO 14001:2015. **Panels have a 50-year warranty.**

Dimensional technical data - tolerances as per UNI EN 12825: class 1

Nominal dimensions	Length	Width	Thickness	Weight	Squareness	Concavity & convexity	Twisting
600x600x29 mm	600 mm	600 mm	29 mm	9,90 kg			
Tolerances	+/- 0,2 mm	+/- 0,2 mm	+/- 0,3 mm	+/- 0,5 kg	+/- 0,3 mm	< 0,4 mm	< 0,3 mm

Mechanical technical data (25x25 mm point loading indentor) on stringerless pedestals.

	Class	Request	Results
UNI EN 12825	Max loading class 4	Max loading not less than 9 kN	Breaking center edge 11,13 kN Breaking center panel 16,10 kN Breaking diagonal 9,67 kN
UNI EN 12825	Deflection class A	Max deflection allowed 2,5 mm	Deflection 2,5 mm center edge at 3,15 kN Deflection 2,5 mm, center panel at 3,31 kN Deflection 2,5 mm, diagonal at 3,45 kN Residual deflection after 30' 0,05 mm

Physical technical data

	Norm	Request	Results
Fire reaction	UNI EN 13501-1 UNI EN 13501-1:2019 SBI EN 13823	Bfl-s1 B-s1-d0	Certificate n. 3000198/RF5975 Istituto Giordano - Italia Certificate N399691 Istituto Giordano - Italia
Fire resistance	UNI EN 13501-2	REI 60r	Certificate CSI 2418 FR + expert advice CSI 0023/ING/ING/22 CSI - Italia
Acoustic performances airborne noise, bare panels	UNI EN 140-12:2001 UNI EN 717-1:2007		Dn,f,w 46 dB PV n. DE 631X857 BBRI - Belgique
Acoustic performances impact noise, bare panels	UNI EN 140-12:2001 UNI EN 717-1:2007		Ln,f,w 69 dB PV n. DE 631X857 BBRI - Belgique
Acoustic performances impact noise inter-floor	UNI EN 140-8:1999		bare Dlw 17 dB rubber+bare Dlw 21 dB rubber+bare+pvc AP Dlw 22 dB rubber+bare+ceramic APB Dlw 29 dB rubber+bare+carpet AP Dlw 28 dB

Environmental data

EPD S-P01016 JVP 4x4	VOC ISO 16000 ISO 16200 Air Comfort Gold Eurofins 392-2018-00137302AEN	FSC INT-COC 001121 FSC-C 023271	Cradle to Cradle Certified BRONZE	Recycled post consume 83% EN 15804+A2 GWP as 1.394 kg CO2 eq / 3.87 per m2.
-------------------------	--	---------------------------------------	--------------------------------------	--

Shipping data

Packaging: dimension 61x61x105 cm wooden pallet & cardboard box high resistance pet banding	Standard packaging 32 panels per pallet gross weight: approx. 320 kg pallet	Identification: printed identification code & light green strip on each panel
---	---	--

M - PEDESTAL

BSEN 12825

M Range of pedestals has been designed to meet the demanding requirements of the BSEN 12825:2001 specification

PEDESTAL GRADE	STUD SIZE	BASE SIZE	VOID RANGE
BSEN 12825	16mm	85x85mm	50-185mm Refer to H Range for voids 186-675 mm



STRINGERS (OPTIONAL); FOR USE IN HIGH VOID AREAS OR SPECIFIC APPLICATIONS



floorplan